

	CONTENT FOR WEBSITE	
GRADE	MRO	Page 1 of 8

Pack Size:

Anti-Seize 57 is ideally available in 500 gm Pack

Overview:

Anti-seize 57 is an Anti-Seize Lubricant is a heavy-duty, high-temperature anti-seize thread compound applicable for heavy pressure applications. It can be used in high temperature areas up to 870°C

Anti-Seize Lubricant is used to lubricate and to permit easy disassembly of assemblies exposed to high temperatures and heavy contact pressures, such as boiler and oven parts, jet engines, and industrial turbines.

Features and benefits:

- High-temperature anti-seize thread compound.
- Applicable to heavy pressure applications.
- Permit easy disassembly of assemblies.

Specification:

Properties

1.)	Chemical Type	:	Synthetic grease
2.)	Odor	:	Petroleum
	Appearance		Aluminum
3.)	Specific Gravity @ 25±2°C	:	1.17
4.)	Brookfield Viscosity @ 25±2°C,	:	250,000 cP
5.)	Particle size ((mm)	:	22.5
6.)	Application	:	Anti-seize Lubricant

Pack Size:

My-T-Kleen® 20-40 is ideally available in 100 ml and 500 ml containers

Overview:

My-T-Kleen® 20-40 is an anti-rust and anti-corrosive aerosol spray. It provides metal surfaces with a long-lasting lubricating film.

Application includes automobile, ships, households, factories, and electric rooms, precision instruments, steel accessories and high sensing elements etc.

- It forms no gum or sludge
- No silicone or harmful chemicals are included
- Decrease the noise caused by rust

Features and benefits:

- Prevents rust & corrosion
- Non-corrosive
- Non-staining
- Leaves no residue
- Ideal for chains & other heavy-use items

Specification:

Properties

1.)	Technology	:	Aerosol
2.)	Appearance	:	Fluorescent green
3.)	Specific Gravity @ 20±2 °C	:	0.78
4.)	pH	:	6-6.5
5.)	Viscosity @ 20 ±2 °C	:	8-15 cP
6.)	Flash point	:	0-40 °C.



CONTENT FOR WEBSITE

GRADE

MRO

Page 3 of 8

7.)	Flammability	:	Highly Flammable
8.)	Solubility in water	:	Negligible
9.)	Evaporation rate	:	Very low
10.)	Odor	:	Distinctive smell of pine oil

	CONTENT FOR WEBSITE	
GRADE	MRO	Page 4 of 8

Pack Size:

My-T-Kleen® 20-70 is ideally available in 100 ml and 500 ml containers

Overview:

My-T-Kleen® 20-70 is a high purity, non-Ozone depleting, nonconductive and quick evaporating electrical contact cleaner is a unique combination of solvents and propellants for removing oil, dirt and moisture from the surface of contact points on small electrical equipment, controls, ignition systems, motors, relays and thermostats.

Features and benefits:

- Easy to clean the electrical contacts using extension tube which reduces the risk of spraying at undesired spots
- Contains no CFC's or non-Ozone depleting ingredients
- Reduced cost of maintaining electrical & electronic equipments.
- Non-conductive

Specification:

Properties

1.)	Technology	:	Aerosol
	Chemical type	:	Organic Solvent
2.)	Appearance	:	Transparent
3.)	Specific Gravity @ 20±2 °C	:	0.70
4.)	pH	:	Neutral
5.)	Viscosity @ 20 ±2 °C	:	1-5 cP
6.)	Flash point	:	0-40 °C.
7.)	Flammability	:	Highly Flammable
8.)	Solubility in water	:	Insoluble



CONTENT FOR WEBSITE

GRADE

MRO

Page 5 of 8

9.) Evaporation rate : 4NABC

10.) Odor : Petroleum

11.) Cleaning Efficiency : Excellent

	CONTENT FOR WEBSITE	
GRADE	MRO	Page 6 of 8

Overview:

My-T-Kleen® Paint and Gasket Remover is a fast-acting blend of solvents for removal of paints, gaskets, adhesives, sealants, lacquers and varnishes without excessive scraping or causing damage to the surfaces. It also cleans stubborn grease, oil, varnish and carbon deposits.

Pack Size:

My-T-Kleen® Paint and Gasket Remover is ideally available in 500ml spray cans.

Features and benefits:

- Protects surface finish from excessive scraping
- Removes gaskets, paints, sealants and varnishes
- Fast acting formula cleans dried grease & oil

Specification:

Properties

1.)	Color	:	Opaque
2.)	Appearance	:	Viscous Liquid
3.)	Specific Gravity @ 20 °C	:	1.05-1.25 g/cm ³
4.)	Vapor Density	:	> Air
5.)	Evaporation rate	:	Faster than n-butyl acetate
6.)	Flash point (aerosol)	:	-18°C (aerosol)
7.)	Corrosivity	:	None
8.)	Solubility in water	:	Nil in water
9.)	Propellant	:	LPG, Non CFC
10.)	Size available	:	500ml

	CONTENT FOR WEBSITE	
GRADE	MRO	Page 7 of 8

Overview:

Protect 77 Spray is a clear, sprayable coating without chlorinated solvents or CFC's. The coating air dries and is tack-free in five minutes to provide a tough environmental, solvent and corrosion resistant coating.

Pack Size:

Protect 77 Spray is ideally available in 500 ml Spray Pack

Features and benefits:

- Free from chlorinated solvents or CFCs.
- Provide a tough environmental and solvent resistant coating
- Air dries tack free in five minutes

Specification:

Properties

1.)	Specific Gravity	:	0.92
2.)	Appearance	:	Clear Liquid
3.)	Service Temperature Range	:	-50 to 100° C
4.)	Viscosity, Brookfield, DV II + Pro, At 25 °C, Spindle 2, Speed 100 rpm	:	20 - 50 cP
5.)	Dielectric Breakdown Voltage, ASTM D149	:	5.8 KV/mm

Overview:

My-T-Shield® 3000 Zinc Flake Spray is a highly reactive spray based on zinc and aluminum flakes, which are surrounded by an inorganic binder giving it an excellent protection against corrosion as in hot dip galvanizing.

Application includes protection of welded structure, auto repairs (underbody), galvanized structure, steel plants and rolling mills, metal pipes and fittings.

Pack Size:

My-T-Shield® 3000 Zinc Flake Spray is ideally available in 500 ml Spray

Features and benefits:

- Provides excellent resistance to Salt Spray test for up to 1500 hrs
- It can be dried accelerated at 40°C-100°C