

TECHNICAL DATA SHEET

My-T-Kleen® 20-40

Anti-Rust and Anti-corrosion Spray

January 2018



METLOK PRIVATE LIMITED
(An ISO 9001 Certified Company)
W- 27, M.I.D.C. Industrial Area
Kalmeshwar – 441 501, Nagpur

Product Description

My-T-Kleen® 20-40 is an anti-rust and anti-corrosive aerosol spray. The product performs anti-rust, lubricating, dehumidifying, decontaminating and eliminating the noise of machinery or other metals, etc., and has a magic effect of uncoiling rust, swiftly looses the rusted screws. My-T-Kleen® 20-40 anti-rust spray can be widely used in places where problem is occurred because of rust. Such as: Automobile, ships, households, factories, and electric rooms, precision instruments, steel accessories and high sensing elements etc. It can infiltrate the areas of rust immediately and slacken rust. It can decrease the noise caused by rust and protect your machine or vehicles.

My-T-Kleen® 20-40 is a synthetic, greaseless all-purpose anti-rust and anti-corrosive aerosol spray that provides metal surfaces with a long-lasting lubricating film. It forms no gum or sludge. Its penetrating agents cut through rust and corrosion to allow free movement of hardware parts. My-T-Kleen 20-40 anti-rust and anti-corrosive aerosol spray is effective in applications as diverse as hardware, household appliances, sporting goods and electrical equipment. No silicone or harmful chemicals are included. Materials such as plastic, fabric, leather, fishing line or paint will not be stained or damaged

Product Features:

- ❖ Prevents rust & corrosion,
- ❖ Keep lubricating
- ❖ Non-corrosive
- ❖ Non-staining
- ❖ Quick drying
- ❖ Leaves no residue
- ❖ Ideal for chains & other heavy-use items
- ❖ Easy application by aerosol spray
- ❖ Protects metal from rust and corrosion, penetrates stuck parts, displaces moisture, and lubricates just about anything.

Functions

1. **Lubricates:** My-T-Kleen® 20-40 lubricating ingredients are widely dispersed and hold to all moving parts. My-T-Kleen® 20-40 does not contain silicone or other additives that attract dust and dirt.
2. **Cleans:** My-T-Kleen® 20-40 gets under dirt, grime and grease to clean while forming a corrosion resistant barrier. It also dissolves adhesives, allowing easy removal of labels. Just spray, wait and wipe.
3. **Protects:** My-T-Kleen® 20-40 protects metal surfaces with corrosion resistant ingredients to shield against moisture and other corrosive elements.
4. **Penetrates:** My-T-Kleen® 20-40 loosens rust stuck to metal bonds and frees stuck, frozen or rusted parts. The lubricating properties of My-T-Kleen® 20-40 then keep these parts working freely.
5. **Displaces Moisture:** My-T-Kleen® 20-40 displaces moisture; it quickly dries out electrical systems to eliminate moisture induced short circuits.

Physical Properties

Technology	Aerosol
Chemical type	Aliphatic and aromatic Solvent
Appearance	Fluorescent green
Propellant Type	Hydrocarbon
pH	6-6.5
Specific Gravity @ 20±2 °C	0.78
Viscosity @ 20 ±2 °C	8-15 cP
Flash point	0-40 °C
Flammability	Highly Flammable
Solubility in water	Negligible
Evaporation rate	Very low
Odor	Distinctive smell of pine oil
Application	Antirust and anti-corrosion coating

Typical Industrial Applications

- ❖ Rusted steel and iron. Pipes, valves, fittings, truck trailers, storage tanks, fences, guardrails, conveyors, supports, overhead cranes, booms, floor gratings, ductwork, agricultural equipment, snow removal equipment, outdoor sign supports, posts, hatch covers
- ❖ It is ideal for hinges, wire ropes and springs, nuts and bolts, motorcycle or bicycle chains, and for undercoating car doors, wheel wells, rocker panels, seams and other metal surfaces exposed to water, dirt or road salt.
- ❖ My-T-Kleen® 20-40 is also great when it comes to cleaning grease, grime, and other marks from most surfaces.
- ❖ Removes grease, oil, lubrication fluids, metal cuttings and fines from parts, equipment and machinery. It is designed to be used as a spray or in immersion cleaning processes, at room temperature or heated.

Other Applications:

Garage

- ❖ Keeps tools from rusting
- ❖ Removes paint, grease and tar from hands
- ❖ Works as a cutting oil on drill bits
- ❖ Dissolves dried paint from spray paint nozzles

Sports

- ❖ Lubricates gears and prevents rust on bikes
- ❖ Keeps fishing lures corrosion free
- ❖ Prevents corrosion on boat hardware
- ❖ Loosens and cleans golf shoe spikes

Automotive

- ❖ Removes bugs, road tar and tree sap
- ❖ Quietness noisy fan belts
- ❖ Cleans alloy wheels

Household

- ❖ Lubricates tracks on sliding doors
- ❖ Cleans tough grease and grime
- ❖ Cleans and polishes stainless steel

Lawn/Garden

- ❖ Lubricates shears, pruners and pop-up sprinklers
- ❖ Cleans grime from patio furniture
- ❖ prevents grass clippings from sticking to mower blades
- ❖ Takes gum out of carpet
- ❖ Removes crayon from walls and doors

Directions for use

1. For best performance gently shake bottle before use.
2. If using on electric equipment or machinery, turn off equipment and wait until surface is thoroughly dry before returning power.
3. Hold container upright 6 or 8 inches from surface.
4. After spraying area to be cleaned allow to dry then wipe or brush clean.
5. Test in small inconspicuous area before applying.

Warnings

1. EXTREMELY FLAMMABLE. Do not store near fire, heated surfaces, sparks, or flames.
2. Read all cautions and directions carefully before using this product.
3. Be certain electric equipment is turned off before cleaning and wait until surface is thoroughly dry before returning power to system.
4. Avoid contact with eyes and skin.
5. Dispose of can in accordance with Federal, State and local regulations.
6. Contents under pressure. Do not store at temperatures over 80°F.
7. Do not puncture or incinerate container.

Pack Size

My-T-Kleen® 20-40 is available in 100 ml and 500 ml containers and may be purchased from your local distributor.

Handling Precautions

My-T-Kleen® 20-40 must be handled in a manner applicable to highly flammable materials and in compliance with relevant local regulations. After use wash hands, avoid contact with eyes and skin. Keep out of reach of children.

Storage

My-T-Kleen[®] 20-40 shall be ideally stored in a cool, dry location in unopened containers at 25±2°C. Store product in a well ventilated area. Keep container closed. For further specific shelf life information, contact our technical service Center.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof.

METLOK PRIVATE LIMITED

(Bonding and Sealing Solutions)

An ISO 9001: 2015 Certified Company

Tel.: 07118-271543/271170/272468

Fax: 07118-272470

Visit us at: www.metlok.in