

## TECHNICAL DATA SHEET

### My-T-Kleen<sup>®</sup> Paint and Gasket Remover

Paint and Gasket Remover

January 2019



METLOK PRIVATE LIMITED  
(An ISO 9001 Certified Company)  
W- 27, M.I.D.C. Industrial Area  
Kalmeshwar – 441 501, Nagpur

#### Product Description

My-T-Kleen<sup>®</sup> Paint and Gasket Remover is a fast-acting blend of solvents for removal of paints, gaskets, adhesives, sealants, lacquers and varnishes without excessive scraping or causing damage to the surfaces. It also cleans stubborn grease, oil, varnish and carbon deposits.

#### Key Properties:

- ❖ Removes gaskets, paints, sealants and varnishes.
- ❖ Fast acting formula cleans dried grease & oil.
- ❖ Protects surface finish from excessive scraping.

#### Application:

- ❖ For removal of baked-on gaskets, gasket cements and formed-in place types of gaskets.
- ❖ For removal of paint, adhesives, lacquers and varnishes without excessive scraping or causing damage to the surfaces.
- ❖ For cleaning stubborn grease, oil, varnish, carbon deposits.

#### Properties of Material

Appearance	: Viscous Liquid
Sp. Gravity @ 20°C	: 1.05-1.25 g/cm <sup>3</sup>
Color	: Opaque
Solubility in water	: Nil in water
Vapor Density	: > Air
Evaporation rate	: Faster than n-butyl acetate
Flash Point (aerosol)	: -18°C (aerosol)
Corrosivity	: None
Propellant	: LPG, Non CFC

#### Directions for Use

Important: Use with adequate ventilation:

1. Mask areas not requiring removal or for protection from overspray.

2. Observe precautions of wearing protective eyewear and hand gloves while handling this product.
3. Spray liberally over surface and allow solvents 5-10 minutes to work for softening paint and then remove with a putty knife or cloth rag.
4. For stubborn or thick coatings, repeat the same procedure.
5. To prevent clogging of actuator and valve dip-tube after use, invert the can and press the actuator button for a short burst till only clear propellant gas comes out.

#### Storage and Shelf Life

1. Store Product in a cool, dry location in unopened containers at 25±2 °C.
2. My-T-Kleen<sup>®</sup> Paint and Gasket Remover will exhibit a shelf life of 12 months from the date of manufacture when stored in above mentioned conditions.
3. Cleaner must be handled in a manner applicable to highly flammable materials and in compliance with relevant local regulations.
4. Special care must be taken to avoid contact of the product or its vapour with naked flame or any electrical equipment that is not flame proofed.
5. The solvent can affect certain plastics or coatings. It is recommended to check all surfaces for compatibility before use.
6. To prevent contamination of unused product, do not return any material to its original container.

#### Pack size

My-T-Kleen<sup>®</sup> Paint and Gasket Remover is ideally available in 500ml spray cans.

#### Caution

1. Contains flammable solvents.
2. Use with adequate ventilation.
3. Do not spray near naked flame, hot surfaces or energized equipment.

---

**Note**

---

All statements, technical information and recommendations set forth herein are based on tests which Metlok Private Limited, believes to be reliable. However, Metlok Private Limited does not guarantee their accuracy or completeness. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In no case will Metlok Private Limited be liable for direct, consequential economic or other damages.

\*\*\*\*\*

**METLOK PRIVATE LIMITED**  
(Bonding and Sealing Solutions)  
An ISO 9001: 2015 Certified Company  
Tel.: 07118-271543/271170/272468  
Fax: 07118-272470  
Visit us at: [www.metlok.in](http://www.metlok.in)